interstuhl

Technical data sheet 100S

Specification Conference stool

Dimensions in mm				
	Seat:	H:	410-510	
		W:	480	
		D:	480	
	Total:			
		H:	600	
		W (no ArmR):	580	
		D:	590	
Packaging data	Weight:	kg	14	
	Volume:	m³	0,31	
Basic equipment				Benefit
Upholstery		Breath actively moulding foam, CFC - CHC- free (segregated foam). Seat: 60 mm, foam + 10 mm decron layer.		Paddings are unglued, ensuring optimal air movement. Breathable.
Sprung column		Sprung column also in lowest position.		Sprung column enables attenuation of the sitting impulse, what saves the spinal column.
Conference glides		Hard conference glides for soft floors.		Optimal standing position of the chair. Protection of the floor.
Base		Aluminium base four legs with conference glides.		High stability, longevity
Metal parts, colour finish		Powder coated white.		With a design very interesting for the eyes.
Materials		All materials are segregated and recyclable.		Environmentally friendly.
Standards		GS-symbol for tested safety and toxic agents.		High security and comfort.
Certification		Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.		High-quality product.
Warranty and return		10 years full warranty. Complete return and recycling guarantee.		Exchange of parts free of charge within the guaranteed period.

interstuhl

Technical data sheet 100S

Specification Conference stool

Covers		Several fabric qualities and leather.		There are various colours and cover materials to choose from for designing the chair.
Base		5-arm aluminium base with castors.		Very high stability, longevity.
Metal parts, colour finish		Metal parts brushed silver, polished.		With a design very interesting for the eyes.
Castors/Glides		Soft conference glides. Hard double castors, load-dependent braked, for soft floors or soft double castors, load dependent braked for hard floors. (acc. to DIN EN 12529).		With castors, the chair does not roll away in an off-loaded condition, minimum risk of accident. With glides, optimal position of the chair, protection of the floor.
Options				Benefit
	Volume:	m³	0,31	
Packaging data	Weight:	kg	14	
		D:	590	
		W (no ArmR):	580	
	Total:	H:	600	
		5.		
		νν. D:	480	
	Seat:	H: W:	410-510 480	
	Conti	ш.	410 E10	