interstuhl

Technical data sheet 23M6

Specification Swivel armchair, Synchronous mechanism

| Dimensions in mm | Backrest: | H: | 655 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 410-515 |
| | | W: | 495 |
| | | D: | 500 |
| | | | |
| | Total: | H: | 1180 |
| | | W (no ArmR): | 560 |
| | | W (ArmR): | 635 |
| | | D: | 740 |
| Packaging data | Weight: | kg | 18 |
| | Volume: | m³ | 0,6 |



Benefit

Basic equipment

| Plastic parts | Seat and back, colour maintained throughout plastic parts, black. | Thus "colourfast" with deep scratches and abrasions. |
|------------------------|---|---|
| Backrest | Upholstered, 30 mm foam, rear of backrest with polypropylene cover | |
| Upholstery | Seat upholstery: 55 mm foam, Upholstery is unglued, ensuring optimal air movement, breathable. | Good seating comfort. |
| Mechanism | Synchronous mechanism. Large opening angle between seat and back until max 117°. | Synchronous mechanism of Interstuhl are designed in a way that they help to support optimally the body in every seating position and also relieve the change between the different deating positions. |
| Seat height adjustment | Seat height adjustment infinitely variable from 410 - 515 mm. Self supporting safety gas spring. | Even those outside the DIN range (i.e. taller than 192 cm and smaller than 151 cm) are offered the correct ergonomic posture. |
| Weight adjustment | From 45 - 120 kg, adjustable within 7 steps. | Individual adjustment of the backrest and back pressure to the size and weight of the user. |
| Castors Ø 65 mm | Hard double castors, black, load dependent braked, for soft floors. (acc. to DIN EN 12529). | The chair does not roll away in an off-loaded position, minimum risk of accident. |
| Base | Colour maintained throughout polyamide base, as colour finish (plastic parts). | Thus "colourfast" with deep scratches and abrasions. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | EN 1335 for office swivel chairs and office swivel armchairs. GS-Symobl for tested safety, tested for contaminants, ergonomics approved, Bifma tested. | High quality product and comfort. |
| Certification | Qualitätsmanagementsystem DIN EN ISO 9001:2008, VO (EG) Nr. 1221/2009 (EMAS), Umweltmanagementsystem DIN EN ISO 14001:2009, OHSAS, EcoVadis Gold, Commitment to sustainability. Quality Office, Blauer Engel, Bifma e3 level Platin. | High quality product. |
| Warranty and return | 10 years warranty. Complete return and recycling guarantee. | Exchange of parts, free of charge, within the guaranteed period. |

interstuhl

Technical data sheet 23M6

Specification Swivel armchair, Synchronous mechanism

| Dimensions in mm | Backrest: | H: | 655 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 410-515 |
| | | W: | 495 |
| | | D: | 500 |
| | | | |
| | Total: | H: | 1180 |
| | | W (no ArmR): | 560 |
| | | W (ArmR): | 635 |
| | | D: | 740 |
| Packaging data | Weight: | kg | 18 |
| | Volume: | m³ | 0,6 |



interstuhl

Technical data sheet 23M6

Specification Swivel armchair, Synchronous mechanism

| Dimensions in mm | Backrest: | H: | 655 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 410-515 |
| | | W: | 495 |
| | | D: | 500 |
| | | | |
| | Total: | H: | 1180 |
| | | | |
| | | W (no ArmR): | 560 |
| | | W (ArmR): | 635 |
| | | D: | 740 |
| | | | 10 |
| Packaging data | Weight: | kg | 18 |
| | Volume: | m³ | 0,6 |



Benefit

Options

| Colour finish | Seat and back incl. base, colour maintained throughout plastic parts, white. | Thus "colourfast" with deep scratches and abrasions. Visual appeal. |
|----------------------------|---|---|
| Castors/Glides | Soft double castors, black/anthracite, load dependent braked, for hard floors or glides. (acc. to DIN EN 12529) | The chair does not roll away in an off-loaded position, minimum risk of accident. |
| Base | Aluminium, brilliant silver powder coated or polished. | Very high stability, long service life. High quality look. |
| Seat depth adjustment | Sliding seat for individual adjustment of the seat depth, adjustment 115 mm | |
| Seat inclination | Adjustable, -3,5° till + 1,5° | The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column. |
| umbar support | Depth- (30 mm) and height adjustable (60 mm). | The lumbar support is depth adjustable and can be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible. |
| rmrests | T-armrest, height adjustable (100 mm), soft surface (as colour finish) 3D T-armrests, height (100 mm) and width (2x25 mm) adjustable, rotatable (2x15°), soft surface (as colour finish) 3D T-armrest, height (100 mm), width (2x25 mm) and depth (50 mm) adjustable, soft surface (as colour finish) | The armrests relieve the neck and shoulder muscles. |
| <i>l</i> leterial (fabric) | Several fabric collections and leather in various colours. | During the design of the cair several colours and upholstery materials are available. |
| wo colour design | For special qualities of cover different colurs are possible on the seat and back upholstery. | Optical design. |