

Catifa 70 Footstool / Sled

Design by Lievore Altherr Molina 2006

Art. 2012: footstool with sled base

Footstool with sled base in chromed steel and polyurethane shell upholstered in leather, faux leather, fabric or customer's fabric. Glides for wooden floors are available upon request.

Dimensions*



* Files CAD 2D - 3D available for download at www.arper.com



product
design
award
2007

Base finishes



CRO
Chrome
finish
steel

Shipment details


Art. 2012	kg	m³	lb	ft³
1 PCS = 1 box	15	0.196	33	6.925

Materials


Fabric by kvadrat and No Stain



Topas 2
67 colors



Hallingdal 65
58 colors



Remix 2
49 colors




Cava 3
49 colors




Flora 2
33 colors



Pro 2
35 colors



Lazio 2
28 colors



Clara
28 colors



Tempo
22 colors



Divina MD
27 colors



Scuba
24 colors




No Stain
34 colors



Divina 3
56 colors



Divina
Melange 2
24 colors



Tonus 3
64 colors



Field
24 colors



Steelcut
Trio 2
49 colors



Sunniva
12 colors




Steelcut 2
37 colors



Pause 4
43 colors



Canvas
28 colors



Savanna
13 colors

Faux leather, Soft leather and chrome free leather by elmo.



PI
Faux
leather
52 colors



PF
Soft
leather
13 colors



ES
Soft leather
Elmosoft®
60 colors

Catifa 70 Footstool / Sled

Design by Lievore Altherr Molina 2006

Options and accessories



1

2

- 1 Polypropylene glide with polyurethane insert
- 2 Polyurethane glide with felt insert

Fire retardant test

UK CONTRACT:
BS7176-07 Medium Hazard: Faux leather.
Elmosoft. Fabric (Flora 2, Pro 2, Divina 3, Divina Melange 2, Hallingdal 65).
BS7176-07 Low Hazard: Soft leather. Fabric (Tonus 3, Topas 2).
UK DOMESTIC:
BS5852-1:1979 Sch.4-5 Part1: Faux leather.
Soft leather. Elmosoft. Fabric (Flora 2, Divina 3, Divina Melange 2, Hallingdal 65, Tonus 3, Topas 2). BS5852-1:1979 Sch. 4 Part1: Fabric (Pro 2).
USA Technical Bulletin 117: Fabric. Faux leather



* For more information on product's certification and environment documents visit www.arper.com or contact us at environment@arper.com