

Technical data sheet C10V

Specification Four legs, not upholstered

Dimensions in mm	Backrest:	H:	430
	Seat:	H:	435
		W:	425
		D:	460
Total:		H:	855
		W (no ArmR):	560
		D:	545
Packaging data	Weight:	kg	6,0
	Volume:	m³	0,37



Basic equipment

Benefit

Seat and Backrest	Seat and backrest wooden shell. Ergonomically-formed waterfall front seat edge.	
Frame	Four legged steel, chromed 18 mm diameter, 2 mm thick steel tube.	
Stackable	Stacking height: 5 pieces. Stacking protection.	Space-saving storage.
Wooden parts	Beech. 9-layerbeech veneer, glued crosswise, ca. 10.5 mm thick.	
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Materials	DIN EN 16139 four leg and cantilever. GS-symbol for tested safety, tested for contaminants.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts, free of charge, within the guaranteed period.

Technical data sheet C10V

Specification Four legs, not upholstered

Dimensions in mm	Backrest:	H:	430	
		Seat:	H:	435
			W:	425
	Total:	D:	460	
		H:	855	
		W (no ArmR):	560	
Packaging data	Weight:	kg	6,0	
		Volume:	m³	0,37



Options	Benefit
Wooden parts	Wood: Oak, American walnut. HPL: black, white. Optical design.
Glides	Felt glides for hard floors, black. Optimum stability of the chair. Spares the floor.
Accessories	Row connector on request.

Technical data sheet C11V

Specification Four legged with seat upholstery

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 445
		W:	425
		D:	460
Packaging data	Total:	H:	855
		W (no ArmR):	560
		D:	545
		Weight:	kg 6,7
	Volume:	m³ 0,37	



Basic equipment

Benefit

Seat and Backrest	Seat and backrest wooden shell. Ergonomically-formed waterfall front seat edge.	
Upholstery	Seat upholstered. Foam 20 mm, thickness of cushion appr. 23 mm.	Great seating comfort.
Frame	Four legged steel, chromed 18 mm diameter, 2 mm thick steel tube.	Very high stability, longevity. High-quality look.
Stackable	Stacking height: 5 pieces. Stacking protection.	Space-saving storage.
Wooden parts	Beech. 9-layerbeech veneer, glued crosswise, ca. 10.5 mm thick.	
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Materials	DIN EN 16139 four leg and chantilever. GS-symbol for tested safety, tested for contaminants.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts, free of charge, within the guaranteed period.

Technical data sheet C11V

Specification Four legged with seat upholstery

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 445
		W:	425
		D:	460
Packaging data	Total:	H:	855
		W (no ArmR):	560
		D:	545
		Weight:	kg 6,7
	Volume:	m³ 0,37	



Options	Benefit
Wooden parts	Wood: Oak, American walnut. HPL: black, white. Optical design.
Glides	Felt glides for hard floors, black. Optimum stability of the chair. Spares the floor.
Accessories	Row connector on request.

Technical data sheet C12V

Specification Four legged with seat and back upholstery

Dimensions in mm	Backrest:	H:	430
	Seat:	H:	445
		W:	425
		D:	420
Total:		H:	855
		W (no ArmR):	560
		D:	545
Packaging data	Weight:	kg	7,2
	Volume:	m³	0,37



Basic equipment

Benefit

Seat and Backrest	Seat and backrest wooden shell. Ergonomically-formed waterfall front seat edge.	
Upholstery	Seat and back upholstered. Foam 20 mm, thickness of cushion appr. 23 mm.	Great seating comfort.
Frame	Four legged steel, chromed 18 mm diameter, 2 mm thick steel tube.	Very high stability, longevity. High-quality look.
Stackable	Stacking height: 5 pieces. Stacking protection.	Space-saving storage.
Wooden parts	Beech. 9-layerbeech veneer, glued crosswise, ca. 10.5 mm thick.	
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Materials	DIN EN 16139 four leg and chantilever. GS-symbol for tested safety, tested for contaminants.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts, free of charge, within the guaranteed period.

Technical data sheet C12V

Specification Four legged with seat and back upholstery

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 445
		W:	425
		D:	420
	Total:	H:	855
		W (no ArmR):	560
		D:	545
Packaging data	Weight:	kg	7,2
	Volume:	m³	0,37



Options	Benefit
Wooden parts	Wood: Oak, American walnut. HPL: black, white. Optical design.
Glides	Felt glides for hard floors, black. Optimum stability of the chair. Spares the floor.
Accessories	Row connector on request.

Technical data sheet C13V

Specification Four legged with extra seat upholstery

Dimensions in mm	Backrest:	H:	430	
		Seat:	H:	445
			W:	425
			D:	420
	Total:	H:	855	
W (no ArmR):		560		
D:		545		
Packaging data	Weight:	kg	7,4	
	Volume:	m³	0,37	



Basic equipment

Benefit

Seat and Backrest	Seat and backrest wooden shell. Ergonomically-formed waterfall front seat edge.	
Upholstery	Seat and backrest with extra seat upholstery. Foam 20 mm, thickness of cushion appr. 23 mm.	Great seating comfort.
Frame	Four legged steel, chromed 18 mm diameter, 2 mm thick steel tube.	Very high stability, longevity. High-quality look.
Stackable	Stacking height: 5 pieces. Stacking protection.	Space-saving storage.
Wooden parts	Beech. 9-layerbeech veneer, glued crosswise, ca. 10.5 mm thick.	
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Materials	DIN EN 16139 four leg and chantilever. GS-symbol for tested safety, tested for contaminants.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts, free of charge, within the guaranteed period.

Technical data sheet C13V

Specification Four legged with extra seat upholstery

Dimensions in mm	Backrest:	H:	430
		Seat:	H: 445
		W:	425
		D:	420
	Total:	H:	855
		W (no ArmR):	560
		D:	545
Packaging data	Weight:	kg	7,4
	Volume:	m³	0,37



Options	Benefit
Wooden parts	Wood: Oak, American walnut. HPL: black, white. Optical design.
Glides	Felt glides for hard floors, black. Optimum stability of the chair. Spares the floor.
Accessories	Row connector on request.

Technical data sheet C14V

Specification Four legged fully upholstered

Dimensions in mm	Backrest:	H:	440
	Seat:	H:	445
		W:	440
		D:	420
Total:		H:	865
		W (no ArmR):	560
		D:	565
Packaging data	Weight:	kg	7,1
	Volume:	m³	0,37



Basic equipment

Benefit

Seat and Backrest	Seat and backrest fully upholstered. Ergonomically-formed waterfall front seat edge, foam 20 mm, thickness of cushion appr. 23 mm.	
Frame	Four legged steel, chromed 18 mm diameter, 2 mm thick steel tube.	Very high stability, longevity. High-quality look.
Stackable	Stacking height: 5 pieces. Stacking protection.	Space-saving storage.
Glides	Plastic glides for soft floors, black.	Optimum stability.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Materials	DIN EN 16139 four leg and cantilever. GS-symbol for tested safety, tested for contaminants.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), Environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability.	High-quality product.
Warranty and return	10 years warranty. Complete return and recycling guarantee.	Exchange of parts, free of charge, within the guaranteed period.

Technical data sheet C14V

Specification Four legged fully upholstered

Dimensions in mm	Backrest:	H:	440	
		Seat:	H:	445
			W:	440
			D:	420
Total:		H:	865	
		W (no ArmR):	560	
		D:	565	
Packaging data	Weight:	kg	7,1	
	Volume:	m³	0,37	



Options

Benefit

Glides Felt glides for hard floors, black.

Optimum stability of the chair. Spares the floor.

Accessories Row connector on request.