

## **Technical data sheet JC216**

Specification Swivel chair medium high, mesh, Synchr.FlexGrid

| Dimensions in mm | Backrest: | H:           | 600     |
|------------------|-----------|--------------|---------|
|                  | Seat:     | H:           | 410-520 |
|                  |           | W:           | 500     |
|                  |           | D:           | 460     |
|                  | Total:    | H:           | 1175    |
|                  |           | W (no ArmR): | 500     |
|                  |           | W (ArmR):    | 725     |
|                  |           | D:           | 630     |
| Packaging data   | Weight:   | kg           | 15,7    |
|                  | Volume:   | m³           | 0,6     |
|                  |           |              |         |



| Basic equipment        |  | Benefit  |
|------------------------|--|--|
| Plastic parts          | Colour maintained throughout, black, light grey.   | Colourfast and resistant to deep scratches and abrasions.  |
| Backrest               | Backrest medium height, mesh-covered, black.   |  |
| Upholstery             | Seat upholstery: 55 mm foam, upholstery is unglued, ensuring optimal air movement, breathable.   | Great seating comfort.   |
| Mechanism              | Synchronous mechanism. Large opening angle between the seat and the backrest of up to 118°.      | Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the chang between the different seating positions.   |
| Seat height adjustment | Seat height adjustment infinitely variable from 410 - 520 mm. Self-supporting safety gas spring. | Even people outside the DIN range (i.e. taller than 192cm and smaller than 151cm) will sit in the most ergonomic way.  |
| Weight Adjustment      | From 45 - 120 kg, adjustable within 7 steps.   | Individual adjustment of the backrest and the back pressure to the weight and height of the user.  |
| Seat depth adjustment  | Individual adjustment of the seat depth, 60 mm adjustment.                                       |  |
| Lumbar support         | Adjustable height and depth.   | Through to a mechanical rotation, the depth of the FlexGrid integrated into the back frame can be adjusted (and the height can be adjusted simply by moving it) and adapted to the anatomical build of the person sitting in the chair. This provides custom support in the lumbar spine area. |
| Castors Ø 65 mm        | Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529).      | The chair does not roll away in an off-loaded situation, minimum risk of accident.   |
| Base                   | Colour maintained throughout polyamide base, black.  | Colourfast and resistant to deep scratches and abrasions.  |
| Chair column           | Column colour matches the base colour.   | Uniform colour scheme for the whole model.   |
| Materials              | All materials are segregated and recyclable.   | Environmentally friendly.  |



## **Technical data sheet JC216**

Specification Swivel chair medium high, mesh, Synchr.FlexGrid

| Backrest: | H:   | 600  |   |
|-----------|--|--|---|
| Seat:     | H:   | 410-520  |   |
|           | W:   | 500  |   |
|           | D:   | 460  |   |
| Total:    | H:   | 1175   |   |
|           | ,  | 500  |   |
|           | W (ArmR):  | 725  |   |
|           | D:   | 630  | I   |
| Weight:   | kg   | 15,7   |   |
| Volume:   | m³   | 0,6  | • 3 •   |
|           | armchairs. GS-S                                      | Symobl for tested safety, tested   | High quality product and great comfort.   |
|           | 9001:2008, VO (<br>Environmental n<br>ISO 14001:2009 | (EG) No. 1221/2009 (EMAS),<br>nanagement system DIN EN<br>I, OHSAS, EcoVadis gold,   | High quality product.   |
|           |  |  | Exchange of parts free of charge within the guaranteed period.  |
|           | Seat: Total: Weight:                                 | Seat: H: W: D: Total: H: W (no ArmR): W (no ArmR): W (ArmR): D: Weight: kg Volume: m³  EN 1335 for offic armchairs. GS-S for contaminants  Quality manager 9001:2008, VO (Environmental no ISO 14001:2008) Commitment to 10 years warran | Seat: H: 410-520 W: 500 D: 460  Total: H: 1175 W (no ArmR): 500 W (ArmR): 725 D: 630  Weight: kg 15,7 |

Disassembly instructions are available upon request for any interstuhl product



## **Technical data sheet JC216**

Specification Swivel chair medium high, mesh, Synchr.FlexGrid

| Dimensions in mm | Backrest: | H:           | 600     |
|------------------|-----------|--------------|---------|
|                  | Seat:     | H:           | 410-520 |
|                  |           | W:           | 500     |
|                  |           | D:           | 460     |
|                  | Total:    | H:           | 1175    |
|                  |           | W (no ArmR): | 500     |
|                  |           | W (ArmR):    | 725     |
|                  |           | D:           | 630     |
| Packaging data   | Weight:   | kg           | 15,7    |
|                  | Volume:   | m³           | 0,6     |



| Options          |   | Benefit  |
|------------------|---|--|
| Castors          | Soft double castors, load dependent braked, for hard floors (Acc. to DIN EN 12529).   | The chair does not roll away in an off-loaded position, minimum risk of accident.                              |
| Base             | Polished aluminium and light-grey plastic   | Very high stability, long service life. High-quality look.   |
| Seat inclination | Adjustment of seat +4,9°  | The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column. |
| Armrests         | 2D T-armrests, adjustable height/width. 3D<br>T-armrests, adjustable height/width/depth, soft.<br>4D T-armrests, adjustable height/width/depth,<br>rotatable, soft. | The armrests relieve the neck and shoulder muscles.  |
| Cover materials  | Various fabric and leather options available.   | Individual design.   |
|                  |   |  |
|                  |   |  |

Disassembly instructions are available upon request for any interstuhl product