

HAWORTH®

Description: Comforto 62

Model

6220

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, seat and back without upholstery, without armrests



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)
Stackability		8 chairs on stacking cart SCT2
Technical details of mechanism		
Mechanism	(standard)	without

Technical details of seat and back

Backrest		plastic, available in 10 standard colours hole pattern for optimum air circulation
Back foam		without
Seat		plastic PP, available in 10 standard colours
Seat foam		without
Exchange of seat and back		possible on site by customer or comforto after-sales service
Armrests		without

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim. gross 21,0 kg net 18,0 kg - 3 units in carton - 650x650x970 mm 0,410 m³

HAWORTH®

Description: Comforto 62

Model

6221

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, seat and back without upholstery, with armrests



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)
Stackability		8 chairs on stacking cart SCT2
Technical details of mechanism		
Mechanism	(standard)	without

Technical details of seat and back

Backrest		plastic, available in 10 standard colours hole pattern for optimum air circulation
Back foam		without
Seat		plastic PP, available in 10 standard colours
Seat foam		without
Exchange of seat and back		possible on site by customer or comforto after-sales service
Armrests		fixed armrests, Soft touch arm caps in black or light grey

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 60 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim.	gross 24,0 kg net 21,0 kg - 3 units in carton	650x650x970 mm	0,410 m ³
------------------------------------	---	----------------	----------------------

HAWORTH®

Description: Comforto 62

Model

6222

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, upholstered seat and back, without armrests



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

like photo but with upholstered seat and back

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction. tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)

Stackability 8 chairs on stacking cart SCT2

Technical details of mechanism

Mechanism	(standard)	without
------------------	------------	---------

Technical details of seat and back

Backrest	plastic, available in 10 standard colours hole pattern for optimum air circulation	
Back pad	fabrics of the currently valid price list with upholstery support out of fiberboard	
Foam seat and back	15 mm CMHR 4055 RG 40, Density	5,5kpa
Seat pad	fabrics of the currently valid price list with upholstery support out of fiberboard	
Exchange of seat and back	possible on site by customer or comforto after-sales service	
Armrests	without	

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007
DIN ISO 14001:2004+COR1:2009
DIN EN 13761
Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim.	gross 30 kg net 27 kg - 3 units in carton 650x650x970 mm 0,410 m ³
------------------------------------	---

HAWORTH®

Fabric selection of different fabrics according to current colour card						
Fabric selection				Abrasions	Quantity of	Fire-retardant according to
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
F2	51	84% PVC-Compound, 16% Bio-Cotton	740 g/sqare/m	-	7	Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.

HAWORTH®

Description: Comforto 62

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, upholstered seat and back, with armrests

Model

6223



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

like photo but with upholstered seat and back

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)
Stackability		8 chairs on stacking cart SCT2
Technical details of mechanism		
Mechanism	(standard)	without

Technical details of seat and back

Backrest		plastic, available in 10 standard colours hole pattern for optimum air circulation
Back pad		fabrics of the currently valid price list with upholstery support out of fiberboard
Foam seat and back		15 mm CMHR 4055 RG 40, Density 5,5kpa
Seat pad		fabrics of the currently valid price list with upholstery support out of fiberboard
Exchange of seat and back		possible on site by customer or comforto after-sales service
Armrests		fixed armrests, Soft touch arm caps in black or light grey

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 60 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001-2008
DIN ISO 14001-2004
GS-certified DIN EN 13761

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim.	gross 33,0 kg net 30,0 kg - 3 units in carton	650x650x970 mm	0,410 m ³
------------------------------------	---	----------------	----------------------

HAWORTH®

Fabric selection of different fabrics according to current colour card						
Fabric selection				Abrasions	Quantity of	Fire-retardant according to
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
		84% PVC-Compound,		-	7	
F2	51	16% Bio-Cotton	740 g/sqare/m			Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.

HAWORTH®

Description: Comforto 62

Model

6224

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, upholstered seat, back without upholstery, without armrests



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

like photo but with upholstered seat

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)

Stackability 8 chairs on stacking cart SCT2

Technical details of mechanism

Mechanism	(standard)	without
------------------	------------	---------

Technical details of seat and back

Backrest	plastic, available in 10 standard colours hole pattern for optimum air circulation
Back pad	without
Foam seat	15 mm CMHR 4055 RG 40, Density 5,5kpa
Seat pad	fabrics of the currently valid price list with upholstery support out of fiberboard
Exchange of seat and back	possible on site by customer or comforto after-sales service
Armrests	without

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007
DIN ISO 14001:2004+COR1:2009
DIN EN 13761
Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim.	gross 24 kg net 21 kg - 3 units in carton 650x650x970 mm 0,410 m ³
------------------------------------	---

HAWORTH®

Fabric selection of different fabrics according to current colour card						
Fabric selection			Abrasions	Quantity of	Fire-retardant according to	
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
		84% PVC-Compound,		-	7	
F2	51	16% Bio-Cotton	740 g/sqare/m			Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.



HAWORTH®

Description: Comforto 62

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, upholstered seat, back without upholstery, with armrests

Model

6225



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

like photo but with upholstered seat

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction tube, Ø 22 x 2 mm in chrome (at an extra charge)
Stackability		8 chairs on stacking cart SCT2
Technical details of mechanism		
Mechanism	(standard)	without

Technical details of seat and back

Backrest		plastic, available in 10 standard colours hole pattern for optimum air circulation
Back pad		without
Foam seat		15 mm CMHR 4055 RG 40, Density 5,5kpa
Seat pad		fabrics of the currently valid price list with upholstery support out of fiberboard
Exchange of seat and back		possible on site by customer or comforto after-sales service
Armrests		fixed armrests, Soft touch arm caps in black or light grey

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 60 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007
DIN ISO 14001:2004+COR1:2009
DIN EN 13761
Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim.	gross 27 kg net 24 kg - 3 units in carton 650x650x970 mm 0,410 m³
------------------------------------	---

HAWORTH®

Fabric		selection of different fabrics according to current colour card				
Fabric selection		Abrasions	Quantity of	Fire-retardant according to		
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
F2	51	84% PVC-Compound, 16% Bio-Cotton	740 g/sqare/m	-	7	Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.

HAWORTH®

Description: Comforto 62

Model

6230

Visitor and seminar chair, stackable, 4-leg tubular welded steel base, glides, weight assistet recline mechanism, seat and back without upholstery, without armrests



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)
Stackability		8 chairs on stacking cart SCT2
Technical details of mechanism		
Mechanism	(standard)	weight assistet recline mechanism

Technical details of seat and back

Backrest		plastic, available in 10 standard colours hole pattern for optimum air circulation
Back foam		without
Seat		plastic PP, available in 10 standard colours
Seat foam		without
Exchange of seat and back		possible on site by customer or comforto after-sales service
Armrests		without

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim. gross 21,0 kg net 18,0 kg - 3 units in carton - 650x650x970 mm 0,410 m³