

HAWORTH®

Description: Comforto 62

Model

6220T

Seminar chair, not stackable, 4-leg tubular welded steel base, glides, seat and back without upholstery, without armrests, writing tablet right or left



Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Filling tray (optional): chromed

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)

Stackability not stackable

Technical details of mechanism

Mechanism (standard) without

Technical details of seat and back

Backrest	plastic, available in 10 standard colours hole pattern for optimum air circulation
Back foam	without
Seat	plastic PP, available in 10 standard colours
Seat foam	without
Exchange of seat and back	possible on site by customer or comforto after-sales service
Armrests	without

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty	5 years
Recycling and disposal	yes, at an extra charge, upon request

Shipping weight/carton dim. gross 00,0 kg net 00,0 kg - carton - 000x000x000 mm 0,000 m³

HAWORTH®

Description: Comforto 62

Model

6222T

Seminar chair, not stackable, 4-leg tubular welded steel base, glides, upholstered seat and back, without armrests, writing tablet right or left



Haworth Design Studio/ Simon Desanta

Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Filling tray (optional): chromed

like photo but with upholstered seat and back

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction. tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)

Stackability not stackable

Technical details of mechanism

Mechanism (standard) without

Technical details of seat and back

Backrest	plastic, available in 10 standard colours hole pattern for optimum air circulation
Back pad	fabrics of the currently valid price list with upholstery support out of fiberboard
Foam seat and back	15 mm CMHR 4055 RG 40, Density 5,5kpa
Seat pad	fabrics of the currently valid price list with upholstery support out of fiberboard
Exchange of seat and back	possible on site by customer or comforto after-sales service
Armrests	without

Detailed measurements

Seat height/total height	43 cm/86 cm
Back height	43 cm
Seat width/total width	49 cm / 56 cm
Seat depth/total depth	47/56 cm
Fabric quantity required	without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty 5 years

Recycling and disposal yes, at an extra charge, upon request

Shipping weight/carton dim. gross 00 kg net 00 kg - carton 000x000x000 mm 0,000 m³

HAWORTH®

Fabric selection of different fabrics according to current colour card						
Fabric selection			Abrasions	Quantity of	Fire-retardant according to	
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
F2	51	84% PVC-Compound, 16% Bio-Cotton	740 g/sqare/m	-	7	Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.



HAWORTH®

Description: Comforto 62

Model

6224T

Seminar chair, not stackable, 4-leg tubular welded steel base, glides, upholstered seat, back without upholstery, without armrests. with writing tablet right or left



Base (standard):

4-leg tubular welded steel base, black or silver metallic (similar to RAL 9006)

Base (optional):

4-leg tubular welded steel base in chrome

Filling tray (optional): chromed

like photo but with upholstered seat

Technical details of base

Glides	(standard)	plastic glides in polyamide, either black or light grey
	(option)	felt glides for parquet or marble floor
Castors	(option1)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for carpet
	(option 2)	dual wheel castors according to DIN EN 12529 black Ø 50 mm for hard floors
Base	(standard)	steel welding construction, tube Ø 22 x 2 mm either in black or silver metallic (similar to RAL 9006), powder-coated
Base	(option 1)	steel welding construction, tube Ø 22 x 2 mm in chrome (at an extra charge)

Stackability not stackable

Technical details of mechanism

Mechanism (standard) without

Technical details of seat and back

Backrest plastic, available in 10 standard colours
hole pattern for optimum air circulation

Back pad without

Foam seat 15 mm CMHR 4055 RG 40, Density 5,5kpa

Seat pad fabrics of the currently valid price list with upholstery support out of fiberboard

Exchange of seat and back possible on site by customer or comforto after-sales service

Armrests without

Detailed measurements

Seat height/total height 43 cm/86 cm

Back height 43 cm

Seat width/total width 49 cm / 56 cm

Seat depth/total depth 47/56 cm

Fabric quantity required without

Certificates

DIN ISO 9001:2008 +BSOHSAS 18001:2007

DIN ISO 14001:2004+COR1:2009

DIN EN 13761

Quality Office

Warranty and recycling

Product warranty 5 years

Recycling and disposal yes, at an extra charge, upon request

Shipping weight/carton dim. gross 00 kg net 00 kg - carton 000x000x000 mm 0,00 m³

HAWORTH®

Fabric selection of different fabrics according to current colour card						
Fabric selection				Abrasions	Quantity of	Fire-retardant according to
Pr. gr./coll.	Material	Weight	Martindale	colours	EN 1021	
F0	34	100% Polyester	560 g/m	50.000	12	Part 1 + 2
F0	50	100% Polyester	470 g/m	50.000	12	Part 1 + 2
F1	22	100% Polyester	680 g/m	80.000	7	Part 1 + 2
F1	23	100% Polyester	530 g/m	80.000	10	Part 1 + 2
F1	25	100% Trevira CS	630 g/m	70.000	12	Part 1 + 2
F1	82	100% Xtreme FR	465 g/m	100.000	60	Part 1 + 2
F2	51	84% PVC-Compound, 16% Bio-Cotton	740 g/sqare/m	-	7	Part 1 + 2
F2	65	90% Wool/10% Nylon	415g/sqare/m	100.000	49	Part 1 + 2
F2	39	95% Wool/5% Polyamid	600 g/m	200.000	12	Part 1 + 2
F3	18	100% Trevira CS	450 g/m	70.000	22	Part 1 + 2
F4	21	100% Trevira CS	510 g/m	80.000	35	Part 1 + 2
F5	58	94% Wool/6% Nylon	710 g/m	80.000	12	Part 1 + 2
F5	94	E-Leather	770 g/m	200.000	6	Part 1 + 2
F6	97	Natural leather		-	9	Part 1 + 2

Attention: The fire-retardancy depends on the upholstery foam quality used.

