

Seater, with permanent height-adjustment by comforto-lift
in any position

Base: Column and adjusting elements in silver metallic (similar to RAL 9006)

Fabric collection	Weight/width 140 cm
Price group 0: 100% Polypropylene FR	Fabric collection 30 350 g/m
Price group 0: 100% Polyacryl	Fabric collection 31 430 g/m
Price group 0: 100% Polyester	Fabric collection 34 430 g/lfdm.
Price group 1: 100% Trevira CS	Fabric collection 12 630 g/m
Price group 1: 81% Polyacryl, 19% Polyester	Fabric collection 35 480 g/m
Price group 1: 100% Xtreme FR®	Fabric collection 82 465 g/m
Price group 1: Imitation leather	Imitation leather 37
Price group 3: 95 % Wool, 5 % Polyamide	Fabric collection 39 600 g/m
Price group 3: 100% Polyester	Fabric collection 84 440 g/m
Price group 3: 100% Worsted wool	Fabric collection 86 520 g/m
Price group 5: 85% wool, 15% Polyamide	Fabric collection 87 520 g/m
Price group 6: 84% Wool, 15% Nylon	Fabric collection 88 690 g/m
Price group 6: 100% Wool	Fabric collection 89 520 g/m
Price group 7: Natural leather	Leather collection 99
Price group 8: Natural leather	Leather collection 97
Price group 8: 60% Nylon, 40% Polyurethane	Fabric collection 95 500 g/m



Design: comforto Team

Seat/backrest	Seater, Ø 32 cm	
Mechanism	-	
Seat height	By comforto-lift from 58 - 87 cm, in any position	
Seat depth adjustment	-	
Forward tilt	-	
Armrests	-	
Total height	58 - 87 cm	
Backrest height	-	
Lumbar adjustment	-	
Seat width/Total width	32 cm / 37 cm	
Seat depth/Total depth	32 cm / 37 cm	
Shipping weight	gross: 9 kg	net: 7,5 kg
Dimensions for shipment in cartons	-	-
Back shell	-	
Upholstery support back	-	
Upholstery support seat	Moulded plywood	
Back foam	-	
Seat foam	Polyether foam, thickness: 60 mm	
Mechanism	Aluminium construction	
Base	Upright column with a base filled with visco-elastic foam	
Castors	-	
Scuff plates	-	
Fabric	Selection of different fabrics according to current colour card	
Quantity of fabric required	0,50 m with a width of 0,50 m	
Electrostatically conductive equipment	-	
Exchange of seat	Possible on site by customer or comforto after-sales service	
Mechanical shock absorber	-	
Norms/standards	DIN EN ISO 9001:2000, DIN EN ISO 14001	
Recycling and disposal	Yes, upon request, at an extra charge	
Product warranty	5 years	