

Stool, with permanent height-adjustment by comforto-lift
in any position

Base: Adjusting elements in silver metallic (similar to RAL 9006)
or, at an extra charge, in chrome

Fabric collection

Price group 0: 100% Polypropylene FR
Price group 0: 100% Polyacryl
Price group 0: 100% Polyester
Price group 1: 100% Trevira CS
Price group 1: 81% Polyacryl, 19% Polyester
Price group 1: 100% Xtreme FR®
Price group 1: Imitation leather
Price group 3: 95 % Wool, 5 % Polyamide
Price group 3: 100% Polyester
Price group 3: 100% Worsted wool
Price group 5: 85% wool, 15% Polyamide
Price group 6: 84% Wool, 15% Nylon
Price group 6: 100% Wool
Price group 7: Natural leather
Price group 8: Natural leather
Price group 8: 60% Nylon, 40% Polyurethane

Weight/width 140 cm

Fabric collection 30 350 g/m
Fabric collection 31 430 g/m
Fabric collection 34 430 g/lfdm.
Fabric collection 12 630 g/m
Fabric collection 35 480 g/m
Fabric collection 82 465 g/m
Imitation leather 37
Fabric collection 39 600 g/m
Fabric collection 84 440 g/m
Fabric collection 86 520 g/m
Fabric collection 87 520 g/m
Fabric collection 88 690 g/m
Fabric collection 89 520 g/m
Leather collection 99
Leather collection 97
Fabric collection 95 500 g/m



Model 0111

Design: comforto Team

Seat/backrest	Round seat, Ø 37 cm	
Mechanism	-	
Seat height	By comforto-lift from 39 - 53 cm, in any position	
Seat depth adjustment	-	
Forward tilt	-	
Armrests	-	
Total height	39 - 53 cm	
Backrest height	-	
Lumbar adjustment	-	
Seat width/Total width	Ø 37cm / 66 cm	
Seat depth/Total depth	Ø 37 cm / 66 cm	
Shipping weight	gross: 9 kg	net: 7,5 kg
Dimensions for shipment in cartons	-	
Back shell	-	
Upholstery support back	-	
Upholstery support seat	Moulded beech plywood	
Back foam	-	
Seat foam	Polyether foam, thickness: 60 mm	
Mechanism	Aluminium construction	
Base	Steel/welding construction, 5-prong base	
Castors	Dual wheel castors according to EN 12529, either carpet or hard floor, braked	
Scuff plates	Polypropylene silver metallic (similar to RAL 9006) or, at an extra charge, in chrome	
Fabric	Selection of different fabrics according to current colour card	
Quantity of fabric required	0,50 m with a width of 0,50 m	
Electrostatically conductive equipment	-	
Exchange of seat	Possible on site by customer or comforto after-sales service	
Mechanical shock absorber	Optionally available at an extra charge	
Norms/standards	DIN EN ISO 9001:2000, DIN EN ISO 14001	
Recycling and disposal	Yes, upon request, at an extra charge	
Product warranty	5 years	